

DECKEER™ TOPPER™



12 VOLT BUCKET TOP SPRAYER

Unit Stores Wet, Avoid problems of solutions drying out becoming hard or sticky. Quick connect on suction hose inlet clicks onto pump outlet for closed loop storage. Accidental running of unit will not damage pump.

Heavy Duty Regulator Adjusts pressure from 20 PSI to 225 PSI. The by-pass return continuously mixes solution.

Heavy Duty 50 AMP On/Off Switch & 20 AMP Fuse Are top mounted for easy operation and service. Unit draws only 5-15 amps, depending on pressure.



27 series deep cycle battery & Power Caddy™ are not included. see page 7

Service & Maintenance Is quick and simple. Pump tool kit is 3/16 hex wrench and your fingers. Pump can be completely renewed to factory new condition in less than 5 minutes. Heavy duty regulator is repaired with finger tips. No need to remove for service, simply unscrew cap, remove piston.

Adjust Spraying Pressure At The Gun!

The pressure regulator on the pump sets maximum spraying pressure. Thumb wheel on the spray gun adjusts pressure downward from maximum set spraying pressure.

Convenient One Hand Portability

Carrying handle holds spray gun. Hoses and harness wrap around motor assembly.



Spray Nozzle Adjusts From fine mist, to straight stream. Spin-on 11/16" nozzle cap allows you to quickly change from one Spraying Systems™ nozzle to another. Optional flat fan, solid cone and tree spray nozzles can be found in the Accessory section of Price List.

Spray Gun All Stainless Steel, brass & viton construction. Quick connect inlet for easy storage. Standard sprayer 15/16" nozzle thread on outlet allows connection of all nozzles and nozzle accessories.

Specifications:

- Model Number: TOPPER-225
- Size: 12.5" x 12.5" x 8"
- Ship Wt.: 20 lbs.

Performance:

- PSI: 20 TO 225
- GPM: 1.5
- AMPS: 3 TO 15 (12V)

PUMPTEC

PUMPTEC, INC.
P. O. BOX 187
ANOKA, MN 55303 USA



PHONE (763) 433-0303
FAX (888) 786-7832
www.pumptec.com