

CHECKER™ HYDROSTATIC TEST UNITS

120 VOLT 1/2 H.P. CHECKER™ HYDROSTATIC TEST UNIT

Featuring: Series 356 Pump, Continuous-Duty Open Drip Proof 1/2 H.P. Motor, 35' Cord With GFCI, Adjustable Pressure Unloader Valve, Liquid Filled Pressure Gauge, Quick Connect Garden Hose Inlet, Quick Connect 3/8 Outlet, Heavy Duty Carry Handle, Heavy Duty Non-Conductive Mounting Rails & Grommets

17A



MODEL NUMBER	PART NUMBER	GPM	PSI	MAX AMPS	DESCRIPTION	LIST PRICE	WEIGHT EACH
HTU-231-1/2HP	80409	3.1	250	8.6	Series 356 Pump 1/2 HP ODP motor GFCI with 35' cord Adjustable pressure unloader Heavy duty handle Heavy duty mounting rails Quick Connect inlet Quick Connect 3/8" outlet	\$595.00	35 lbs

120 VOLT 3/4 H.P. CHECKER™ HYDROSTATIC TEST UNIT

Featuring: Series 356 Pump, Continuous-Duty Totally Enclosed Fan Cooled 3/4 H.P. Motor, 35' Cord With GFCI, Adjustable Pressure Unloader Valve, Liquid Filled Pressure Gauge, Quick Connect Garden Hose Inlet, Quick Connect 3/8 Outlet, Heavy Duty Carry Handle, Heavy Duty Non-Conductive Mounting Rails & Grommets

17B



MODEL NUMBER	PART NUMBER	GPM	PSI	MAX AMPS	DESCRIPTION	LIST PRICE	WEIGHT EACH
HTU-431-3/4HP	80410	3.1	400	11.6	Series 356 Pump 3/4 HP TEFC motor GFCI with 35' cord Adjustable pressure unloader Heavy duty handle Heavy duty mounting rails Quick Connect inlet Quick Connect 3/8" outlet	\$645.00	38 lbs

GAS ENGINE CHECKER™ HYDROSTATIC TEST UNIT

Featuring: Series 357 Pump, 3.5 H.P. Tecumseh 4-Cycle Engine, Adjustable Pressure Unloader Valve, Quick connect Garden Hose Inlet, Quick Connect 3/8" Outlet, Easy Lift Carry Handle.

17C



MODEL NUMBER	PART NUMBER	GPM	PSI	MAX AMPS	DESCRIPTION	LIST PRICE	WEIGHT EACH
HTU-532-GAS	80412	3.2	500	2400	Series 357 Pump 3.5 H.P. Tecumseh 4 cycle engine Quick Connect inlet, garden hose Quick Connect outlet, 3/8" Adjustable pressure unloader Carry handle & mounting rails	\$615.00	45 lbs

* PRICES SUBJECT TO CHANGE WITHOUT NOTICE *

CHECKER™

120 VOLT, 3/4 H.P. HYDROSTATIC TEST UNIT

See Page

17B

1500 PSI Pump

Series 356 Factory Set To 500 PSI Maximum,
Adjustable Down to 50 PSI Maximum.

Heavy Duty Handle

Epoxy-Coated With Grip.

On-Off Switch

Protected From Moisture
And Physical Damage.

Continuous-Duty

Totally Enclosed Fan
Cooled 3/4 H.P. Motor.

Pressure Gauge

0-600 PSI Liquid Filled
Industrial Grade.

Adjustable Pressure

0-500 PSI With By-Pass
Unloader Valve.

Quick Connect

3/8 NPT (F) Outlet
Connects Easily To
Test Components.

Non-Conductive Mounting Rails

Rust Proof With Heavy
Duty Pads. Keeps Unit
High And Dry When
Used Outdoors.

Quick Connect

Garden Hose
Connects In
A "Snap".

Safe GFCI Protection

Electricity To Unit Is Automatically
Shut-Off If Any Short Occurs.

35' Cord

SJTW Weather Resistant UL.

Specifications:

- Model Number: HTU-431-3/4HP
- Size: 18" x 10" x 12"
- Ship Wt.: 38 lbs.

Performance:

- PSI: 50 To 400
- Max GPM: 3.1
- Max AMPS: 11.6 (120V)

PUMPTEC

PUMPTEC, INC.
P. O. BOX 187
ANOKA, MN 55303 USA



PHONE (763) 433-0303
FAX (888) 786-7832
www.pumptec.com