

SERIES 314U

PUMP MATERIALS

Pump Body: Nylon
 Plunger: 304SS
 Seals: Proprietary U-cup
 Elastomers: Viton

SPECIFICATIONS

Flow: to 4.0 GPM
 Pressure: to 200 PSI
 Temperature: to 120°F
 RPM(max): 2400
 Inlet: 3/8 F NPT(2)
 Outlet: 3/8 F NPT(2)

Sprayer pump for applications up to 4 GPM, 200 PSI



PN	MODEL	GPM	PSI	NOZZLE	AMP	Weight (lbs.)
80730	314U-190/M30	2.64	70	20	19.5	23
		2.49	110	15	25.3	23

SERIES 314T

PUMP MATERIALS

Pump Body: Nylon
 Plunger: 304SS
 Seals: Teflon Blend.
 Elastomers: Viton

SPECIFICATIONS

Flow: to 4.0 GPM
 Pressure: to 200 PSI
 Temperature: to 120°F
 RPM(max): 2400
 Inlet: 3/8 M NPT(2)
 Outlet: 3/8 M NPT(2)

Sprayer pump for applications up to 4 GPM, 200 PSI



PN	MODEL	GPM	PSI	NOZZLE	AMP	Weight (lbs.)
80731	314T-190/M30	2.64	70	20	19.5	23
		2.49	110	15	25.3	23