

SERIES 348U

PUMP MATERIALS

Pump Body: Teflon hard coated aluminum
 Plunger: 304SS
 Seals: Proprietary U-cup
 Elastomers: Viton

SPECIFICATIONS

Flow: to 4.0 GPM
 Pressure: to 400 PSI
 Temperature: to 120°F
 RPM(max): 2400
 Inlet: 1/2 F NPT(2)
 Outlet: 1/2 F NPT(2)

Sprayer pump for applications up to 4 GPM, 400 PSI



PN	MODEL	GPM	PSI	NOZZLE	AMP	Weight (lbs.)
80050	348U-190/M30	2.64	70	'20	19.5	23
		2.49	110	'15	25.3	23

PN	MODEL	GPM	PSI	NOZZLE	AMP	Weight (lbs.)
80040	348U-190/M224	2.74	75	'20	21.4	28
		2.60	120	'15	28.5	28
	Intermittent duty only	2.34	220	'10	40.4	28

PN	MODEL	GPM	PSI	NOZZLE	AMP	Weight (lbs.)
80066	348U-190/M50	2.83	80	'20	25.9	30
		2.70	130	'15	33.2	30
		2.35	220	'10	45.9	30
	Intermittent duty only	2.20	280	'08	53.8	30

9025 Multi-function Control System

The unique design of the 9025 maintains nearly constant pressure in spray or bypass thereby protecting the electrical system from high amperage draw during bypass...the most common cause of 12 VDC system failure.

The 9025 is unique in the industry because it is specifically designed for the 12 VDC pest control and turf sprayer industry.

