

SERIES 356U

PUMP MATERIALS

Pump Body: Teflon hard coated aluminum
 Plunger: 304SS
 Seals: Proprietary U-cup
 Elastomers: Viton

Tree sprayer pump for applications up to 4 GPM, 500 PSI

SPECIFICATIONS

Flow: to 4 GPM
 Pressure: to 500 PSI
 Temperature: to 120°F
 RPM(max): 2400
 Inlet: 1/2 F NPT(2)
 Outlet: 1/2 F NPT(2)



| PN | MODEL | GPM | PSI | NOZZLE | AMP | Weight (lbs.) |
|-------|--------------|------|-----|--------|------|---------------|
| 80070 | 356U-190/M60 | 2.91 | 85 | '20 | 31.5 | 45 |
| | | 2.7 | 130 | '15 | 37.6 | 45 |
| | | 2.4 | 230 | '10 | 50.0 | 45 |
| | | 2.19 | 300 | '08 | 61.0 | 45 |
| | | | | | | |
| PN | MODEL | GPM | PSI | NOZZLE | AMP | Weight (lbs.) |
| 80192 | 356U-190/M26 | 3.0 | 90 | '20 | 27.1 | 49 |
| PN | MODEL | GPM | PSI | NOZZLE | AMP | Weight (lbs.) |
| 80077 | 356U-190/M96 | 2.81 | 140 | '15 | 34.1 | 47 |
| | | 2.50 | 250 | '10 | 44.2 | 47 |
| | | 2.26 | 320 | '08 | 53.3 | 47 |
| | | 2.00 | 450 | '06 | 66.4 | 47 |

9025 Multi-function Control System

The Six port design, three on the pressure side plus three on the bypass side, provides maximum plumbing configuration flexibility.

You can mount controls where you want them, in any location...simply, with four screws.

