

RO TANK

Truck Mount Reverse Osmosis system from
Pure Rinse Systems, Inc.



- High rejection RO membranes remove 99% of tap water impurities
- Epoxy coated steel frame with modular components
- Vibration mounting
- 115 VAC pumping system

PN	Weight (lbs.)
50003	200



RO Tank specifications

Feature	Description
Capacity	110 gallon tank
Carbon Filter	10" x 4" Carbon
Final Filter	10" x 4.25", 1 micron depth, poly
Membranes	Thin film composite, high rejection
Housings	PVC and glass-filled polyester resin
Pumps	Pumptec model 348, 2.5 GPM, 200 PSI
Motors	1/2 HP, 115/230 VAC, 7.2/3.6 FLA, 1.15 SF
Regulators	Pumptec 500-200, adj. 0-200 PSI
Gauges	Industrial grade, glycerine filled, SS bodies
Size	21"D x 62"W x 45"H
Weight	200 lbs. dry

RO Trolley

Ultimate Window Cleaning Unit



- 3000 gal. (11,000 ltr.) per day capacity
- Triple prefiltration
- 50 gallon storage tank
- High rejection membranes
- High capacity PUMPTEC pumps
- 18" Hose reel
- 300' non-marking hose
- 3 pole capability and up to four stories high



PN	Weight (lbs.)
50007	300

* poles not included

RO Trolley specifications

Capacity	3000 GPD (water@ 77°F)
Carbon Filter	10" x 4" Carbon
Final Filter	10" x 4.25", 1 micron depth
Membranes	Thin film composite, high rejection
Housings	PVC and glass-filled polyester resin
Pumps	Pumptec model 356, 2.5 GPM, 200 PSI
Motors	1/2 HP, 115/230 VAC, 7.2/3.6 FLA, 1.15 SF
Regulators	Pumptec 500-200, adj. 0-200 PSI
Gauges	Industrial grade, glycerine filled, SS bodies
Hose	18" reel with 300 ft. of non-marking hose, integral hose guide
Size	32"D x 57"W x 52"H

RO Anywhere

Compact, high performing, reverse osmosis unit.
Perfect for window, carpet, tile or grout cleaning.



- To 2700 gal. (10,000 ltr.) per day capacity
- Triple prefiltration
- High rejection membranes
- High capacity PUMPTEC pumps

PN	Capacity
50001	900 GPD
50012	1800 GPD
50006	2700 GPD



RO Anywhere specifications

Feature	Description
Capacity	2700 GPD (water@ 77°F)
Carbon Filter	10" x 4" Carbon
Final Filter	10" x 4.25", 1 micron depth
Membranes	Thin film composite, high rejection
Housings	PVC and glass-filled polyester resin
Pumps	Pumptec model 348, 2.5 GPM, 200 PSI
Motors	1/2 HP, 115/230 VAC, 7.2/3.6 FLA, 1.15 SF
Regulators	Pumptec 500-200, adj. 0-200 PSI
Gauges	Industrial grade, glycerine filled, SS bodies
Hose	18" reel with 300 ft. of non-marking hose, integral hose guide
Size	15"D x 30"W x 37"H
Weight	150 lbs. dry