

Series 114T & 114V - 200 PSI

Inlets:	1/2" Barb and 3/8" (M) NPT
Outlets:	1/4" (M) NPT (2)
MAX RPM:	2000
MAX PSI:	200
MAX GPM:	2.0
MAX Temp:	140°F
SEALS:	Teflon (T) or NBR (V)
Body	Grilon
Plunger	Stainless Steel
Valves	Acetal
Fasteners	Stainless Steel



114/M35

12 volt pump and motor sets

PN	Volts DC	Model	Max Flow	Max PSI	Max HP	Max Amps	Weight (lbs.)
80287	12 VDC	114T-075/M15	1.5	200	0.15	15	10
80326	12 VDC	Spray Basic	1.5	200	0.15	15	13
80286	12 VDC	114T-075/M9	1.5	100	0.08	9	8

120 volt pump and motor sets

PN	Model	PSI Spray	Nozzle Size	GPM Spray	AMPS Spray	Weight (lbs.)
80007	114V-085/M35	200	'03	.67	1.2	10
80647	114V-075/M36	200	'03	.67	1.1	11
80083	114T-075/M35	200	'04	.89	1.4	10
80215	114T-075/M36	200	'04	.89	1.1	11
80085	114V-085/M33	120	'04	.69	0.9	8
80057	114T-075/M33	100	'06	.95	0.9	8

230 volt - 50/60 HZ pump and motor sets

PN	Model	PSI Spray	Nozzle Size	GPM Spray	AMPS Spray	Weight (lbs.)
80142	114V-085/M85	200	'03	.67	0.6	10
80672	114V-085/M72•	200	'03	.67	0.5	11
80219	114T-075/M85	200	'04	.89	0.7	10
80218	114T-085/M72•	200	'04	.89	0.6	11

• 50 Hz only

100 volt pump and motor sets

PN	Model	PSI Spray	Nozzle Size	GPM Spray	AMPS Spray	Weight (lbs.)
80676	114V-085/M52	200	'03	.67	1.3	10
80675	114T-075/M52	200	'04	.89	1.5	10