

## Series 348U — 0 - 1000 PSI

Inlets:	3/8" (F) NPT (2)
Outlets:	3/8" (F) NPT (2)
MAX RPM:	1750
MAX PSI:	1000
MAX GPM:	3.0
MAX Temp:	140°F
SEALS:	NBR
Body	Hardcoat Aluminum
Plunger	Stainless Steel
Valves	Stainless Steel
Fasteners	Stainless Steel



348/M81

### 120 volt pump and motor sets

PN	Model	PSI Spray	Nozzle Size	GPM Spray	AMPS Spray	Weight (lbs.)
80171	348U-090/M74	1000	'02	1.0	9.7	28
80483	348U-130/M81	1000	'03	1.5	11.5	30
80014	348U-090/M75	800	'02	.9	7.2	28
80709	348U-150/M81	800	'04	1.8	11.5	30
80252	348U-140/M74	700	'04	1.7	10	28
80710	348U-210/M81	600	'06	2.3	11.5	30
80013	348U-140/M75	300	'06	1.7	7.2	28

*Pumptec's compact powerful pumps make possible portable hard surface cleaning equipment. The efficiency and performance of the pump systems power the rotary cleaning heads without the high power draw and mechanical complexity of other type of pumps. Pumptec's oil-less crankcase design eliminates the embarrassment of leaking oil from equipment onto a customer's floor.*

**Pumptec** made portable  
hard surface cleaners **possible.**