

# Series 356U — 0 - 1200 PSI

Inlets:	3/8 (F) NPT (2)
Outlets:	3/8 (F) NPT (2)
MAX RPM:	1750
MAX PSI:	1200
MAX GPM:	3.0
MAX Temp:	140°F
SEALS:	NBR
Body	Anodized Aluminum
Plunger	Stainless Steel
Valves	Stainless Steel
Fasteners	Stainless Steel



356U-M64

## 120 volt pump and motor sets

PN	Model	PSI Spray	Nozzle Size	GPM Spray	AMPS Spray	Weight (lbs.)
80011	356U-190/M64	1200	'04	2.2	15	48
80711	356U-200/M64	1000	'045	2.3	15	48
80712	356U-230/M64	800	'06	2.7	15	48

## 230 volt - 50/60 Hz pump and motor sets

PN	Model	PSI Spray	Nozzle Size	GPM Spray	AMPS Spray	Weight (lbs.)
80712+	356U-230/M64	1200	'04	2.2	7.5	48
80711+	356U-200/M64	800	'03	1.8	6.0	48

+ Motor 120/230V, 50/60 Hz. Must be wired by customer for 230V. Note: Performance for 50 Hz. Consult Pumptec for applications with 60 Hz.

## Hard Surface Pump Set



- Hard surface cleaner with your extractor
- Affordable and durable
- Plugs into any 15 amp outlet

PN	Model	PSI Spray	Nozzle Size	GPM Spray	AMPS Spray	Weight (lbs.)
80346	356U-180/M44	1200	'04	2.2	15	56